



CHANNEL & SUPPORT SYSTEMS

Back To Back Shallow Channel

Part Code	Length (m)	Finish
UC4142/3	3	Galvanized to BS EN10346
UC4142/6	6	Galvanized to BS EN10346
GMUC4142/3	3	Hot Dipped to BS EN ISO 1461
GAUC4142/6	6	Hot Dipped to BS EN ISO 1461

Span (m)	0.50	0.75	1.00	1.50	2.00	2.50	3.00
Deflection at load *mm	1.00	2.30	4.10	9.20	16.40	25.60	36.80
Safe UDL **kg	736	489	365	240	177	138	112




Solid Channel in stock, slotted on request.

Back To Back Deep Channel

Part Code	Length (m)	Finish
UC4182/3	3	Galvanized to BS EN10346
UC4182/6	6	Galvanized to BS EN10346
GMUC4182/3	3	Hot Dipped to BS EN ISO 1461
GMUC4182/6	6	Hot Dipped to BS EN ISO 1461

Span (m)	0.50	0.75	1.00	1.50	2.00	2.50	3.00
Deflection at load *mm	0.50	1.10	2.00	4.60	8.20	12.80	18.40
Safe UDL **kg	2372	1579	1186	784	583	462	380



Solid Channel in stock, slotted on request.

Back To Back Shallow Channel Slotted

Part Code	Length (m)	Finish
UC4142S/3	3	Galvanized to BS EN10346
UC4142S/6	6	Galvanized to BS EN10346
GMUC4142/3	3	Hot Dipped to BS EN ISO 1461
GMUC4142/6	6	Hot Dipped to BS EN ISO 1461

Span (m)	0.50	0.75	1.00	1.50	2.00	2.50	3.00
Deflection at load *mm	0.50	1.10	2.00	4.60	8.20	12.80	18.40
Safe UDL **kg	2372	1579	1186	784	583	462	380

