



UNITRUNK

SECTION 10: STEEL CONDUIT (CLASS 4)

Rigid steel conduit conforms to the following specification relating to cable management systems: BS 4568 part 1: 1970 Clauses 4, 5.1, 5.4, 6.1, 7.1, 7.2, 8 and 9, BS EN 61386-21:2004 Clauses 7.1, 7.5, 8.1, 8.2, 9.1, 10.3, 10.4, and 14.2.2.3 (high protection).

The base structure is 20mm (or 25mm or 32mm) seam welded steel tube processed from hot rolled steel strip.

BS 4568 heavy protection is achieved by the hot dipped galvanising method to the thickness required under BS 4568 and EN 50086.



ACCREDITED TO THE FOLLOWING STANDARDS:



132

HOW TO ORDER

GA - CON - 25
Finish Product Type Diameter

Steel Conduit (Class 4)



Galvanised

Part Code	Description
GACON20	20mm Conduit 3.75m
GACON20/3	20mm Conduit 3m
GACON25	25mm Conduit 3.75m
GACON25/3	25mm Conduit 3m
GACON32	32mm Conduit 3.75m

IMPORTANT - Supplied in 3000mm & 3750mm lengths as standard, threaded both ends with a coupler attached at one end. Available in 20 - 25mm diameter and 32mm diameter on request. Sold in packs of 8.

QuickFix Trunking

QuickFix Multi Compartment Trunking

Lighting Trunking

Uniklip Cable Tray

Speedway Cable Ladder Pre-Galv. Cable Ladder

Cable Basket Systems

Channel & Support

Floor Trunking

Bench Outlet & Perimeter Trunking

Steel Conduit (Class 4)

Innovative Design Solutions

Accessories & Supports

Index