

## Unitrunk Skirting Trunking

Easily fitted and available with all the necessary bends, etc. to form a complete installation. Types S1 and S2 are designed for installation after wall and floor surfaces have been completed. Tee pieces, Threshold Units, Pier Sets, etc. can be supplied to customer requirements.


The body and divider of the standard skirting trunking are manufactured from galvanised sheet steel to BS EN 10346:2015.

The cover is made from galvanised sheet steel and can be finished in epoxy/polyester coating of any colour on request. All trunking is supplied in 3m lengths as standard, complete with joining plates and screws.

S1 and S2 trunking is supplied with compartments as shown and is therefore suitable for carrying mains, telephone and VDU or other low voltage circuits. The dividers have provision every 200mm along the length, with 20mm EKO's to allow access between compartments. A Back Box is also available on request for complete segregation.

It is normal practice to run the mains circuit in the larger compartment as the cover can be punched to accept a standard 13 amp socket or other accessory. Alternatively a short section of cover can be supplied with one or two gang socket outlet. Socket plates and accessories are manufactured to overlap at the edges.

### Standard Skirting Trunking



Part Code	Description
S1/2	2 compartment (150mm x 43mm)
S1/3	3 compartment (150mm x 43mm)
S2/2	2 compartment (200mm x 43mm)
S2/3	3 compartment (200mm x 43mm)

Other sizes available on request.

### Skirting Blank End

Part Code	Description
S1BELH	Left Hand
S1BERH	Right Hand
S2BELH	Left Hand
S2BERH	Right Hand



Left Hand



Right Hand